

SN 10/621,249

ATTORNEY DOCKET NO. SUYE:001

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. Canceled.

2. (Currently amended) A manufacturing method for a resin product having flow patterns, comprising:

an injection molding process of injection-molding a resin material, obtained by compounding a solid base material having a given ground color, and a solid colorant material having brightness and/or a hue different from that of the ground color, by means of an injection molding machine ~~having a cylinder and a screw so that flow patterns based on the ground color of the base material and the colorant material appear on the surface~~ thereby obtaining an injection molded article having the flow patterns based on the ground color of the base material and the colorant material appear on the surface; and

a colored clear coating process of spreading a colored clear paint of a color different from the ground color of the base material over the surface of the injection-molded article having the flow patterns so that the respective hues of the ground color and the flow patterns and the hue of the colored clear paint are combined, ~~to be~~ thereby obtaining a resin product having the flow patterns adjusted to a desired product color.

3. (Original) A manufacturing method for a resin product having flow patterns according to claim 2, wherein the colorant is a composite material formed of a plurality of colorants having different colors.

4. (Original) a manufacturing method for a resin product having flow patterns according to claim 2 or 3, wherein the base material is compounded with a sheen material.

5. (Currently amended) A manufacturing method for a resin product having flow patterns according to claim 2, wherein the injection-molding machine has a cylinder and a screw, and the temperature of the region near a material supply section of the cylinder of the

SN 10/621,249

ATTORNEY DOCKET No. SUYE:001

injection molding machine is set to be lower than the temperature of the region near a nozzle of the cylinder.

6. (Original) A manufacturing method for a resin product having flow patterns according to claim 5, wherein the moving speed of the screw of the injection molding machine in the axial direction is set to be lower in the initial stage of movement than in the late stage of movement.

7. (New) A manufacturing method for a resin product having flow patterns according to claim 2, wherein the colorant material is formed of a material which is resistant to merging with the base material, thereby preventing excessive fusion with the base material.

8. (New) A manufacturing method for a resin product having flow patterns according to claim 2, wherein the resin product is a wood-grained product in which the ground color is green, the colorant material is a darker colored material, and the colored clear paint is brown.